



Insulator:	PPS
Fiammability:	UL 94V-0
Sleeve:	Brass
Mating pin Ø:	0.41 mm
Mechanical life:	min 500 cycles
Rated cument:	1A
Contact resistance:	max 10 m Ω
Dielectric strength:	min 1000V RMS

MPHCM - X - X - X - X - X - X - 00

① ② ③ ④ ⑤ ⑥ ⑦

- | | |
|---|---|
| <p>① MPHCM series</p> <p>② Contact NO:
XX=XXpin
For example:
06=06pin</p> <p>③ Pin Plated
0; No
1; Tin 150 μ"
2; Tin 200 μ"
3; G/F
4; Gold 3 μ"
5; Gold 10 μ"
6; Gold 15 μ"
S; Special</p> | <p>④ Packing
A:Tray B:Bag
C:Tube D:Tape Reel</p> <p>⑤ Type selection
A:Type1 B:Type2
C:Type3 D:Type4</p> <p>⑥ Series number
00</p> |
|---|---|

X ± 0.35 X.XX: ± 0.20
X.X: ± 0.25 X.XXX: ± 0.15

UNIT:

	DATE	TIME
--	------	------

DATE
22/03/2018

DATE 02/02/2001



Antenna

ANTENK ELECTRONICS CO., LTD
Http://www.antenk.com
E-mail:sales@antenk.com

**Machined Pin connectors 1.27 mm:
MPHCM series**

MPHSM-XXXX00

MPHSM-XXXX00

REV	DESCRIPTION	DATE